

PLAINTIFF'S ORIGINAL COMPLAINT AND JURY DEMAND

Plaintiff Jewel Jet, LP brings this action for patent infringement against Defendant Sy Kessler Sales, Inc. and alleges as follows:

THE PARTIES

- 1. Plaintiff Jewel Jet, LP is a limited partnership organized and existing under the laws of Texas, having its principal place of business at 5028 Village Circle, Dallas, Texas 75248.
- 2. Upon information and belief, Defendant Sy Kessler Sales, Inc. is a corporation organized and existing under the laws of Texas, having its principal place of business at 10455 Olympic Drive, Dallas, Texas 75220, where it may be served.

JURISDICTION AND VENUE

3. This action arises under the Patent Laws of the United States, Title 35 of the United States Code and the laws of Texas. This Court has subject matter jurisdiction over this action under 28 U.S.C. § 1338(a), which confers jurisdiction over cases of patent infringement, 28 U.S.C. §1331, which confers federal question jurisdiction, and U.S.C. § 2201(a), which

confers jurisdiction over declaratory judgment actions. The Court has supplemental jurisdiction over the Texas state law claims under 28 U.S.C. § 1367.

- 4. Personal jurisdiction exists generally over Defendant because its principal place of business is in the Northern District of Texas. Upon information and belief, personal jurisdiction also exists specifically over Defendant because it makes, uses, sells, offers for sale, and/or imports products covered by Plaintiff's patent within the State of Texas and within the Northern District of Texas.
 - 5. Venue is proper in this Court under 28 U.S.C. §§ 1391(b) and (c) and 1400(b).

PATENT INFRINGEMENT

- 6. Plaintiff incorporates by reference all allegations in paragraphs 1-5 as though fully set forth herein.
- 7. Plaintiff is the owner of all right, title, and interest in and under United States Patent Number 7,257,319 B1 ("the '319 Patent"), entitled "Jewelry Cleaning Device," which duly and legally issued on August 14, 2007. A true and correct copy of the '319 Patent is attached hereto as **Exhibit A**.
- 8. The '319 Patent describes and claims apparatuses and methods for cleansing small items, including jewelry, coins, and trinkets.
 - 9. The '319 Patent is valid and enforceable.
- 10. On or before April 28, 2006, Plaintiff arranged to have products covered by the claims of the '319 Patent manufactured in China for sale in the United States and elsewhere.
- 11. Upon information and belief, subsequent to Plaintiff's arrangement, Defendant arranged for the same manufacturer in China to produce infringing devices for Defendant for sale in the United States and elsewhere.

- 12. Subsequently, Defendant has infringed the claims of the '319 Patent by making, using, importing, selling, and/or offering to sell products that fall within the scope of the claims of the '319 Patent in or into the United States, without authority, including, but not limited to, Defendant's "GemOro Brilliant Spa" and "GemOro UltraSteam" products (collectively "the Infringing Products").
- Products in or into the United States, without authority, Defendant has directly infringed the claims of the '319 Patent under 35 U.S.C. §271(a). Furthermore, by making, using, importing, selling, and/or offering for sale Infringing Products in or into the United States, without authority, the Defendants have also induced infringement of the '319 Patent under 35 U.S.C. § 271(b), and have contributed to the infringement of the '319 Patent under 35 U.S.C. § 271(c). The infringing devices have no substantial non-infringing uses.
- Defendant has offered for sale the Infringing Products in a Jeweler Industry Distributors Association trade magazine, a copy of which is attached hereto as **Exhibit B**. Defendant has also offered for sale the Infringing Products through the Defendant's own sales materials; a copy of a sales brochure is attached hereto as **Exhibit C**. Defendant has also offered for sale the Infringing Products through Defendant's website at http://www.sykessler.com/.
- 15. On or about August 2007, Plaintiff sent a letter notifying Defendant of the existence of the '319 Patent and requesting that Defendant cease and desist all infringing activities. Nonetheless, upon information and belief, Defendant has recklessly continued its infringing activities. Thus, Defendant's infringing conduct constitutes willful infringement.
- 16. As a direct and proximate result of Defendant's acts of patent infringement,
 Plaintiff has been and continues to be injured and has sustained and will continue to sustain

substantial damages in an amount not presently known.

17. Plaintiff has no adequate remedy at law against these acts of patent infringement.

Unless Defendant is permanently enjoined from its unlawful and willful infringement of the '319

Patent, Plaintiff will suffer irreparable harm.

ATTORNEYS' FEES

18. Defendant's deliberate actions make this an exceptional case and Defendant should be required to pay Plaintiff's reasonable costs and attorneys' fees in accordance with 35 U.S.C. § 285.

JURY DEMAND

19. In accordance with Federal Rules of Civil Procedure 38 and 39, Plaintiff asserts its rights under the Seventh Amendment of the U.S. Constitution and demands a trial by jury on all issues so triable.

PRAYER FOR RELIEF

Plaintiff respectfully requests that judgment be entered in its favor and against Defendant and that the Court grants the following relief to the Plaintiff:

- A. Declare that the claims of the '319 Patent are valid and enforceable;
- B. Declare that the Defendant has infringed the claims of the '319 Patent;
- C. Award damages to Plaintiff to which it is entitled for patent infringement;
- D. Enter a preliminary and thereafter a permanent injunction against Defendant's direct infringement of the '319 Patent;
- E. Enter a preliminary and thereafter a permanent injunction against Defendant's active inducements of infringement and/or contributory infringements of the '319 Patent by others;

- F. Award interest on Plaintiff's damages; and
- G. Such other relief as the Court deems just and proper.

DATED January 23, 2008.

Respectfully Submitted,

Michael W. Shore (SBN 18294915) Justin B. Kimble (SBN 24036909)

Shore Chan Bragalone LLP 325 N. St. Paul Street, Suite 4450 Dallas, Texas 75201 Telephone (214) 593-9110 Facsimile (214) 593-9111

ATTORNEYS FOR PLAINTIFF JEWEL JET, LP



(12) United States Patent Clarke

(10) Patent No.:

US 7,257,319 B1

(45) Date of Patent:

Aug. 14, 2007

(54) JEWELRY CLEANING DEVICE

(76)	Inventor:	Michael E. Clarke, 2729 Woodson Dr.,
		McKinney TX (US) 75070

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/758,341

(22) Filed: Jan. 15, 2004

(51) Int. Cl. F17C 7/04 B08B 3/00

(2006.01)

(2006.01)

(58) Field of Classification Search 392/386, 392/387, 394, 396, 397, 398, 403, 404, 405, 392/406; 134/102.1, 102.2

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

377,228 A	1/1888	Bartlett
965,724 A	7/1910	Moneuse
1,587,950 A	6/1926	Hare
1,835,283 A	12/1931	Crickmer
1,878,560 A	9/1932	Wier
2,624,618 A	1/1953	Gelles et al.
2,753,212 A	7/1956	Autlman
2,861,838 A	11/1958	Wyatt et al.
3,039,454 A	6/1962	Gilbertson et a
3,119,004 A	1/1964	Hoop
3,135,987 A	6/1964	Huch
3,348,468 A	10/1967	Eisendrath
3,675,449 A	7/1972	Bluestein
4,114,194 A	9/1978	Walter
4,204,465 A	5/1980	Knecht
4,402,257 A	9/1983	Marotta
D271,145 S	10/1983	McNaughton
4,414,037 A	11/1983	Friedheim
4,632,024 A	12/1986	Cortese

4,761,850	A *	8/1988	Romeo et al 15/323
4,792,174	A *	12/1988	Shioda 296/37.12
4,870,982	A	10/1989	Liu
4,941,490	Α	7/1990	Gross
4,949,738	A	8/1990	Hubbard
5,017,759	Α	5/1991	Baldacci
5,042,954	A	8/1991	Banks
5,209,784	Α	5/1993	Bellman
5,534,741	A	7/1996	Smith
5,988,190	A	11/1999	Borges
6,129,097	\mathbf{A}	10/2000	Papandrea
6,293,187	B1	9/2001	Zils
6,550,862	B2 *	4/2003	Kain 297/250.1
D474,565	S	5/2003	Pinchuk et al.


* cited by examiner

Primary Examiner-Sang Paik

ABSTRACT

A jewelry cleaning device which emits a jet of steam under manually operable control means for the cleansing of various types of small items including jewelry, coins, trinkets, or the like. The jewelry cleaning device of the present invention is lightweight and relatively compact in size thus enabling its use on virtually any conventional tabletop and is easily stored when not in use. The steam generator is powered by conventional electrical power and is controlled by means of a thermostat to maintain the water/steam mixture at a predetermined temperature while in operation. Safety mechanisms include a pressure relief valve to automatically expel steam from the generator when the internal pressure thereof exceeds a predetermined level and a thermal fuse configured in a series connection with the heating element of the steam generator. A containment device is optionally provided which is made of screen mesh and fashioned into a cup-like shape, is slidably engaged onto the sidewall of the jewelry cleaning device housing and is disposed underneath the spout in such a manner to trap gems or other small parts which are inadvertently dislodged from the jewelry piece during the cleaning operation.


18 Claims, 4 Drawing Sheets



U.S. Patent Aug. 14, 2007

Sheet 1 of 4

US 7,257,319 B1



U.S. Patent

Aug. 14, 2007

Sheet 2 of 4

US 7,257,319 B1





FIG. 3



10

FIG. 4

U.S. Patent

Aug. 14, 2007

Sheet 3 of 4

US 7,257,319 B1




FIG. 5

U.S. Patent

Aug. 14, 2007

Sheet 4 of 4

US 7,257,319 B1




FIG. 6







FIG. 7



100 103 FIG. 9








FIG. 12

1

JEWELRY CLEANING DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable.

FIELD OF THE INVENTION

This invention relates to steam cleaning devices, and ¹⁰ more particularly, to a jewelry cleaning device utilizing a jet of steam which is suitable for personal use.

BACKGROUND OF THE INVENTION

Rings, bracelets, necklaces, watches, gems, earrings, and the like present a collection of various types of jewelry which many people today own and wear due to their aesthetically pleasing appearance. Nevertheless through daily wear, this jewelry can become dirty and tarnished thus diminishing their sightly appearance. Therefore, these items must be periodically cleaned in order to maintain their original beauty. Liquid jewelry cleaning formulations which have been developed for this purpose have enjoyed limited success, due mainly to the fact that several common forms of dirt and grime are unaffected thereby. Steam cleaning devices on the other hand have been known for a long time as a valid means of thoroughly cleaning most forms and dirt and grime from jewelry pieces; however, the use of these steam cleaning devices for jewelry items have largely been relegated to jewelry stores and other similar commercial establishments due to their rather large size and complicated

A number of steam cleaning devices have been developed 35 which disclose a means of cleaning jewelry via a relatively high velocity stream of water vapor or steam and examples of such devices includes U.S. Pat. No. 2,753,212 to Aultman, and U.S. Pat. No. 4,414,037 to Friedheim. In addition, U.S. Pat. No. 4,941,490 to Gross discloses a jewelry cleaning means utilizing a high velocity stream of air mixed with a relatively low temperature cleaning solution. Although all of these devices provide an effective method of cleaning jewelry, they suffer in that they are of complex design thus rendering them cost-prohibitive for personal use. Moreover, these complex designs which have been relegated to commercial use have further compounded the problem of complexity in that more stringent safety mechanisms are necessary due to their operation in a commercial environment, thereby further raising their costs. This is due in part to the 50 fact that their use in a commercial environment has necessitated relatively large sized mechanisms which are able to handle high levels of usage.

Auxiliary mechanisms for steam cleaning devices that have been developed to provide a containment structure for jewelry items being cleaned include U.S. Pat. No. 4,949,738 to Hubbard and U.S. Pat. No. 6,129,097 to Papandrea. Each of these devices discloses a means of insuring that small gems which are inadvertently dislodged from the jewelry piece remain within a containment structure during the cleaning process. Similarly to the large steam cleaning devices to which they are attached, these devices are large bulky items and thus generally unsuitable for personal use.

Thus, there has been a long-felt need for a jewelry cleaning device which is sufficiently small and simple in 65 design to enable its use in a residential environment. Moreover, the device's simple, non-complex construction should

2

thus be inexpensive to produce as well as easy to maintain thereby enabling the personal use thereof.

SUMMARY OF THE INVENTION AND OBJECTIVES

The present invention provides a solution to these as well as other needs via a jewelry cleaning device which is small and inexpensive to produce thereby allowing its usage in a residential environment. The device generally comprises a steam generator in fluid communication with a spout which emits a high velocity jet of steam under manually operable control means whereby jewelry items may be effectively 15 cleaned thereby. The jewelry cleaning device of the present invention is lightweight and relatively compact in size thus enabling its use on virtually any tabletop and is easily stored when not in use. The steam generator is commensurately small in size thus minimizing the severity of any safety hazard produced via any of the potential failure modes thereof. The steam generator is powered by conventional electrical power and is controlled by means of a thermostat to maintain the water/steam mixture at a predetermined temperature while in operation. Safety mechanisms include a pressure relief valve to automatically expel steam from the generator when the internal pressure thereof exceeds a predetermined level and a thermal fuse configured in a series connection with the heating element of the steam generator.

Optionally, a containment device is provided in order to trap gems or other small parts which are inadvertently dislodged from the jewelry piece during the cleaning operation. The containment device, which is made of screen mesh and fashioned into a cup-like shape, is slidably engaged onto the sidewall of the jewelry cleaning device and is disposed underneath the spout in such a manner that the entire jet of steam passes therethrough. The mesh of the screen is sufficiently fine to trap any sized gem on its upper surface yet allows the steam stream to easily pass therethrough.

One aspect of the present invention contemplates a jewelry device that is inexpensive to produce and maintain. The present invention utilizes a steam generation means having a design that has been approved for use in residential environments by unskilled operators though the supervisory safety regulatory agencies, yet heretofore has not been known to the art of jewelry cleaning. The present invention's design also differs from the prior known steam cleaning devices for jewelry in that the supervisory regulatory agencies do not require periodic maintenance or inspection thereof, thus further reducing costs. In addition, the relatively small size and lightweight design provides for inexpensive materials costs as well as inexpensive shipping and handling costs.

Another aspect of the present invention is a jewelry cleaning device that is easy to use. The jewelry cleaning device has relatively few moving parts and requires no adjustment mechanisms, thereby allowing use by an unskilled user. The temperature within the steam generator is automatically controlled in order to maintain a constant pressure thereby obviating the need for user adjustment, whereby a consistent spray pattern is always available to the user upon demand. In addition, the present invention exists as a compact space-efficient package, not having any bulky elongated flexible hoses or other cable control structures attached thereto. This compact design also provides for easy storage of the device when not in use.

It is therefore an object of the present invention to provide a jewelry cleaning device which is relatively inexpensive to produce as well as to maintain, thereby enabling the personal use thereof.

A further object of the present invention is to provide a 5 jewelry cleaning device utilizing a pressurized steam generation means to deliver a relatively high velocity jet of steam requiring no external adjustment mechanisms in order to enable its use by an unskilled user.

A related object of the present invention is to provide a 10 jewelry cleaning device which is relatively compact in size thereby allowing the easy storage thereof when not in use.

Another object of the present invention is to provide a jewelry cleaning device having a gem containment means for the trapping of small gems which become dislodged 15 from the jewelry piece during the cleaning operation that is relatively small and lightweight and is releasably attachable thereto.

These and other objects of the present invention will become readily apparent to those familiar with the construc- 20 tion and use of steam cleaning devices and will become apparent in the following portions of the specification, wherein the detailed description is for the purpose of fully disclosing preferred embodiments of the invention without placing limitations thereon.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to 30 the following descriptions taken in conjunction with the accompanying drawings in which:

FIG. 1 is a perspective view of a preferred embodiment of the present invention showing the entire device as a self-

FIG. 2 is a front elevational view of the embodiment of FIG. 1.

FIG. 3 is a side elevational view of the embodiment of FIG. 1.

FIG. 4 is a rear elevational view of the embodiment of 40 FIG. 1 showing a vertically oriented, elongated depression in the rear sidewall into which tongs are releasably disposed.

FIG. 5 is an elevational cross-sectional view of the embodiment of FIG. 2 taken at 5-5

FIG. 6 is a plan view of the slidably removable catch 45 basket of the embodiment of FIG. 1.

FIG. 7 is a side elevational view of the slidably removable catch basket of FIG. 6.

FIG. 8 is a side elevational view of the valve actuator button of the embodiment of FIG. 1.

FIG. 9 is a front elevational view of the valve actuator button of FIG. 8.

FIG. 10 is a plan view of the rocker arm of the embodiment of FIG 1

FIG. 11 is a side elevational view of the rocker arm of 55

FIG. 12 is a front elevational view of the rocker arm of FIG. 10.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in FIGS. 1 through 4, a jewelry cleaning device embodying a preferred embodiment of the instant invention is designated generally by reference numeral 10. The jew- 65 elry cleaning device is generally shown having a housing for enclosing a steam generator (to be described later), a pres-

sure safety cap 85, a valve actuator button 100, and a steam tube 64 for directing a jet of steam downwards through a removable catch basket 30. The steam tube 64 has a terminating end 65 which is constricted in order to emit the steam at a relatively high velocity. The valve actuator button 100 is selectively operable by a user to cause a momentary burst of steam to emanate from the terminating end 65 of the steam tube 64. The space directly below the terminating end 65 of the steam tube 64 which includes the relatively high velocity jet of steam that is above the catch basket 30 defines a cleaning zone 17 whereby jewelry or other small items may be cleaned thereby. The catch basket is provided to trap small gems which may inadvertently become dislodged during the cleaning operation.

The housing shown generally comprises an upper wall 11, and left 12, right 13, rear 14, front 15, and bottom 21 sidewalls made of any thermoplastic material, preferably polypropylene. The front sidewall 15 is generally concave in shape having an aperture 16 proximate the upper wall 11 thereof for receipt of the steam tube 64 therethrough. The front sidewall 15 is generally concave in shape in order to conform to the lateral space defined by the cleaning zone and to minimize the lateral distance which the steam tube must protrude beyond the front sidewall. The front sidewall 15 also has a catch basket retaining member 18 which extends laterally across the front wall 15 having a slot 19 formed therein to slidably receive the rim 32 of the catch basket 30. The front edge of the upper wall 11 is integrally attached to the front sidewall 15 to define an adjoining edge 20 which is chamfered in order to create an aesthetically pleasing finish. In addition, the aesthetic appeal of the housing is further enhanced by the multi-tiered contour of the left 12 and right 13 sidewalls. The rear sidewall sidewall 14 is selectively removable in order to provide access to the contained unit suitable for use on a conventional tabletop. 35 contents of the housing. The rear sidewall 14 is removably attached via screws 23 which are inserted through cupshaped depressions 22 in the rear sidewall 14 and anchored to pedestals 24 which are integrally attached to the left 12 and right 13 sidewalls as best shown in FIG. 5. The jewelry cleaning device 10 of the present invention also includes an elongated depression 26 disposed in the rear sidewall 14 for placement of tongs 27 therein. The tongs 27 provide a means of holding the jewelry piece during the cleaning operation. The width of the depression 26 is chosen such that the tongs 27 are removably held therein with a snug fit. A finger access depression 28 is included which is adjoined to the elongated depression 26 in order to allow easy access to the tongs 27 by a user.

The catch basket 30 which is shown in greater detail in 50 FIGS. 6 and 7, has a screen member 31 formed into a hemi-ellipsoid shape whose upper edge is attached to a rim 32. The rim 32 comprises an annular ring portion 33 which extends around the entire circumference of the screen 31 and a lip portion 34 which is integrally attached to the ring portion 33 for slidable insertion into the slot 18. FIGS. 1 through 3 show the catch basket in the inserted position, however, the user may optionally remove the catch basket from the housing by pulling the catch basket 30 away from the housing, thereby enabling the cleaning of larger items or for the efficient storage thereof.

As shown in FIG. 5, the steam generator includes a canister portion 41 made of any metal, preferably aluminum, which has a maximum water holding capacity of up to approximately 16 ounces of fluid, and most preferably about 8 ounces of fluid. The canister portion 41 has a cup-shaped neck member 42 which is integrally attached to a generally frusto-conical shaped body member 43, and a bottom mem-

ber 44 which is removably attached to body member 43 with a heat resistant gasket 46 sandwiched therebetween to form a pressure tight chamber for the heated steam/water mixture. Removable attachment of the bottom member 44 to the body member 43 is provided by bolts 47 which extend through apertures formed in the bottom member 44 as well as apertures formed in flanges 51 which are integrally attached to body member 43. Conical shaped depressions 54 in the walls of the body member 43 allow access to the associated nuts of the bolts 47. A pedestal 60 is provided for support of 10 the canister 41 within the housing. The pedestal 60 is integrally attached to the bottom member 44 and extends downward therefrom to the bottom sidewall 21 and is secured thereto with bolt 61.

The bottom member 44 has an annular slot 56 for housing a ring-shaped heater element 57 therein. The heater element 57 is preferably an 800 watt calrod device. The bottom member 44 also has a thermostat 58 mounted thereto which is electrically connected to the heater element 57 via a series 20 connection which turns on power to the heater element when the canister temperature drops below a first predetermined threshold and turn off power when the temperature goes above a second predetermined threshold. To prevent thermal runaway of the canister temperature due to a failure of the 25 thermostat, a thermal fuse 59 which is mounted to the bottom member 44 and thus in thermal communication thereto is also configured in a series connection with the heater element 57 to create an electrically open circuit if the temperature of the canister goes above a predetermined temperature, preferably about 450 degrees Fahrenheit. The heater element 57, thermostat 58, and thermal fuse 59 define an electrical circuit which terminates in an electrical cord (not shown) for connection to a suitable source of electrical

The neck member 42 has a valve body 62 integrally formed therein to provide for selective communication of the steam from the canister to the steam tube 64. The valve body 62 has an aperture 66 disposed at its lower end in order to provide fluid communication from the canister 41 into the 40 valve body 62. Steam flow through the aperture 66 is regulated by a valve pin assembly which is slidably received in a hollow shaped plug 67 having an o-ring 68 disposed therebetween to prevent the leakage of steam therethrough. The upper end of the inner wall of the valve body 62 is 45 threaded to threadably receive the plug 67 wherein the head 69 thereof is hexagonally shaped in order to facilitate insertion via a conventional wrench. The valve pin assembly generally includes a pin head 71 which is screwably connected to a connecting rod 72 having a seat flange 73 attached at its lower extremity. A thermally resistant valve seat 74 which is attached to the bottom surface of the seat flange 73 using any suitable adhesive is springably biased against the aperture 66 via compression spring 75. Thus, communication of the steam through the valve is inhibited 55 when no external force is placed upon the pin head 71. Conversely, when a generally upward directing force acts on the pin head 71, the valve is opened and steam is allowed to flow freely from the canister to the steam tube 64. A tube-shaped projection 78 is integrally attached to the neck 60 member 42 having an aperture 79 therebetween, wherein projection 78 has threads on its inner surface to threadably receive the steam tube 64 therein. The steam tube 64 is preferably made from a thermoplastic material such as polypropylene to minimize the amount of heat conduction to 65 the outer perimeter thereof due to hot steam passing therethrough.

Integrally formed with the neck member 42 is a fill tube 81 which extends vertically thereabove. The fill tube 81 extends slightly above the bottom wall of a cup-shaped depression 25 and is held in place with a snug water-tight fit with a grommet 82 therebetween. The depression 25 is integrally attached to the upper wall 11 of the housing having a predetermined diameter to accommodate the bottom edge of the pressure safety cap 85 with an air gap 83 therebetween. The fill tube 81 has internal threads to threadably receive the external threads of the safety valve portion 86 of the pressure safety cap 85. The safety valve portion 86 generally comprises a cylindrical pressure relief housing 87 made preferably of brass, having a generally disk-shaped member 88 integrally attached thereto. An o-ring 84 which extends around the periphery of the housing 87 and abuts member 88 thereunder serves to prevent the leakage of steam past the housing 87. The bottom end of pressure relief housing has a seat having an aperture 90 therein for receipt of a small ball valve member 89 which is springably biased to the closed position. A compression spring 91 exerts a downward force on ball member such that when the internal pressure within the canister exceeds a predetermined pressure, preferably less than 15 psi, the steam may be vented therefrom. Vent holes 93 disposed in member 88 allow the steam within housing 87 to pass through to the ambient environment. The pressure safety cap 85 also comprises a shroud portion 95 for hand screwing of the valve portion to and from the fill tube 81. The shroud portion 95 comprises a generally inverted cup-shaped member 96 made of any 30 material, preferably polypropylene, having an annularshaped valve mount member 97 integrally attached thereto for securement of the safety valve portion 86 via a press fit.

Manual control of the jet of steam is provided by a valve actuator button 100 disposed within a rectangular shaped hole 101 in the upper wall 11 proximate the rear edge thereof in conjunction with a rocker arm 107. The valve actuator button 100 constructed of any material, preferably plastic, comprises a body portion 102 having two arms 103 which depend downward from and are integrally attached thereto as best shown in FIGS. 8 and 9. Both of the arms 103 have holes 104 formed therein for receipt of a pintle bolt 105 therethrough. The rocker arm 107 acts to translate the vertically directing downward force of the button 100 to a generally upward directing force on the pin head 71 of the valve pin assembly via fulcrum member 116. The rocker arm 107 is comprised of a an elongated section of sheet metal having a generally inverted U-shaped cross-section defining top 108, and side walls 109 which terminate at proximal 112 and distal 113 ends. The top wall 108 has a circular shaped hole 115 formed therein through which the fill tube 81 extends. Two fulcrum members 116 depend from and are integrally attached to each of the side walls 109 which rest upon the surface of the neck member 42 thereby allowing the rocker arm 107 to pivot about its axis. Holes 118 exist in each side wall 109 proximate the proximal end 112 thereof for providing a rotatable connection to the arms 103 of button 100 via bolt 105. Similarly, holes 120 exist in each side wall 109 proximate the distal end 113 thereof for providing a rotatable connection the pin head 71 via bolt 121. Thus, when a downward force on the button 100 is applied by a user, the button consequently rotates the rocker arm 107 about fulcrum member 116 and lifts the valve pin assembly thereby opening the valve.

To use, the pressure safety cap 85 is temporarily unscrewed from the device 10 and a predetermined volume of water which is less than the maximum water holding capacity of the canister is poured into the canister 41 via the

fill tube 81. It is to be understood that the maximum water holding capacity is slightly less than the absolute volumetric capacity of the canister so that the water level does not extend above the aperture 66 of the valve body 62. Next, the pressure safety cap 85 is screwed onto the fill tube 81 and the electrical cord connected to a suitable source of electrical power. As electrical power is applied to the heater element 57, the steam generated thereby raises the pressure within the canister to a level which is maintained in equilibrium by the thermostat 58. When equilibrium of the steam/water 10 mixture has been achieved, the device 10 is ready to use. A jewelry piece is placed within the cleaning zone 17 using tongs 27 and the actuator button 100 pressed by a user thereby causing a jet of steam to be emitted from the tube 64 and enveloping the jewelry piece to be cleaned. Failure 15 protection mechanisms include a pressure safety valve which automatically releases steam from the canister 41 if the internal pressure of the canister exceeds a predetermined level and a thermal fuse 59 which automatically opens the circuit to the heater element 57 if the temperature exceeds a 20 predetermined level.

The present invention may be embodied in other specific forms without departing from the spirit or scope of the invention. For example, although the present disclosure described a means of cleaning jewelry, is well known in the 25 art that other small items may be cleaned by immersion in the jet of steam such as coins, trinkets, or the like. Therefore, the described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

I claim:

- 1. An apparatus for cleaning small items such as jewelry 35 using a jet of steam, said device comprising:
 - a steam generator disposed within a housing means, said steam generator having a sealable canister for holding a heated water and steam mixture under pressure;

heating means to heat said sealable canister;

- a manually operated valve which is attached to said sealable canister, wherein said manually operated valve provides selective communication of said steam from said sealable canister to;
- a generally rigid steam tube which is attached to said 45 manually operated valve for communicating said steam to the terminating end of said steam tube, said terminating end of said steam tube is oriented vertically such that said jet of steam is adapted to be projected generally downward in direction, said terminating end is 50 adapted to emit said jet of steam to the ambient environment, whereby the space defined by said jet of steam defines a cleaning zone whereby small items such as jewelry may cleaned by immersion therein; and.
- a catch basket which is disposed on said housing means, said catch basket having a screen member which is disposed underneath said terminating end of said steam tube and oriented to laterally traverse said jet of steam to trap small gems which may inadvertently become 60 dislodged by said jet of steam during the cleaning operation while simultaneously allowing said jet of steam to pass freely therethrough;
- wherein said housing means comprises a front sidewall, said front sidewall having an aperture for receipt of said 65 steam tube therethrough, said front sidewall being concave in shape in order to conform to the lateral

- space defined by said cleaning zone and to minimize the lateral distance which said steam tube projects beyond said front sidewall.
- 2. The apparatus of claim 1, wherein said heating means is automatically controlled by a thermostat, said thermostat is mounted to said sealable canister wherein said thermostat controls the pressure of said water and steam mixture within said sealable canister.
- 3. The apparatus of claim 1, wherein said manually operated valve is manually operable by a valve actuator button means disposed on said housing means, thereby obviating the need for remotely positioned manually operated valves requiring cumbersome cabling structures.
- 4. The apparatus of claim 1, wherein said steam tube is made of a thermoplastic material.
- 5. The apparatus of claim 1, wherein said sealable canister further comprises a pressure safety valve means for automatically releasing said steam in said sealable canister to ambient environment if the pressure in said sealable canister exceeds a predetermined level.
- 6. The apparatus of claim 5, wherein said predetermined level of pressure in sealable canister is less than 15 psi.
- 7. The apparatus of claim 1, wherein said sealable canister has a maximum water holding capacity of up to 16 ounces of fluid.
- 8. The apparatus of claim 1, wherein said catch basket further comprises slidable insertion means for removable attachment to said housing means.
- 9. The apparatus of claim 1, wherein said housing means the invention is therefore, indicated by the appended claims 30 further comprises tong holding means for the efficient and easily accessible storage of conventional tongs
 - 10. A method for cleaning small items such as jewelry using a jet of steam, said steps comprising:
 - providing a steam generator having a sealable canister for holding a heated water and steam mixture under pressure, heating means to heat said sealable canister, a manually operated valve which is attached to said sealable canister, wherein said manually operated valve provides selective communication of said steam from said sealable canister to a generally rigid steam tube which is attached to said manually operated valve for communicating said steam to the terminating end of said steam tube, said terminating end of said steam tube is oriented vertically such that said jet of steam is adapted to be projected generally downward in direction, said terminating end is adapted to emit said jet of steam to the ambient environment, whereby the space defined by said jet of steam defines a cleaning zone, wherein said housing means comprises a front sidewall, said front sidewall having an aperture for receipt of said steam tube therethrough, said front sidewall being concave in shape in order to conform to the lateral space defined by said cleaning zone and to minimize the lateral distance which said steam tube projects beyond said front sidewall;
 - connecting said heating means to a suitable source of electrical power:
 - actuating said manually operated valve thereby causing a jet of steam to be emitted from said terminating end of said steam tube; and,
 - immersing said small item to be cleaned in said cleaning
 - 11. The method of claim 10, wherein said steam generator is disposed in a housing means, said housing means having a catch basket disposed thereon, said catch basket having a screen member which is disposed underneath said terminating end of said steam tube and oriented to laterally traverse

said jet of steam to trap small gems which may inadvertently become dislodged by said jet of steam during the cleaning operation while simultaneously allowing said jet of steam to pass freely therethrough.

- 12. The method of claim 10, wherein said heating means 5 is automatically controlled by a thermostat, said thermostat is mounted to said sealable canister wherein said thermostat controls the pressure of said water and steam mixture within said sealable canister.
- 13. The method of claim 10, wherein said manually 10operated valve is manually operable by a valve actuator button means disposed on said housing means, thereby obviating the need for remotely positioned manually operated valves requiring cumbersome cabling structures.
- 14. The method of claim 10, wherein said steam tube is 15 made of a thermoplastic material.

10

- 15. The method of claim 10, wherein said sealable canister further comprises a pressure safety valve means for automatically releasing said steam in said sealable canister to ambient environment if the pressure in said sealable canister exceeds a predetermined level.
- 16. The method of claim 15, wherein said predetermined level of pressure in sealable canister is less than 15 psi.
- 17. The method of claim 10, wherein said sealable canister has a maximum water holding capacity of up to 16
- 18. The method of claim 10, wherein said catch basket further comprises slidable insertion means for removable attachment to said housing means.

JEWELRY INDUSTRY DISTRIBUTORS ASSOCIATION

WINTER 2007

JIDA 2008 Annual Meeting & Merchandise Day

President's Message

Executive Director's Message

JIDA Fall Visitation

2008 Agenda

2008 Registration Form

ADVERTISERS

Reimers Electra Steam, Inc. 5


Sy Kessler Sales/ Renata

Energizer 11

L&R Manufacturing Co. 12



230 Homewood Drive Butler, PA 16001 Phone (724) 285-8428 Fax (724) 285-8750 lendig@yahoo.com www.jida.info



The JIDA 2008 Annual Meeting & Merchandise Day will be held at the Innisbrook Resort and Golf Club – May 14-17, 2008.

Deluxe Guest Rooms \$159; Executive Suites \$169; and One Bedroom Suites \$179. The Guest rooms are 300 square feet; Executive Suites are 800 sq. ft. and the One Bedroom Suites are 980 sq. ft.

Call 800-456-2000 for reservations at Innisbrook and ask for the JIDA block. Note the Cut-Off Date is 5 p.m. local time on April 13, 2008. All reservations made after that time will be accepted at the resort's prevailing rate, based on availability.

Many amenities are offered at this beautiful golf resort. There are five restaurants at Innisbrook to choose from, as well as four championship golf courses, six swimming pools,11 har tru tennis courts, and after all that overindulgence, there are massage therapists.

Innisbrook is located northwest of the Tampa International Airport — Travel distance is 24 miles from the airport. Mark your calendars now and don't miss this wonderful opportunity to combine business and pleasure.

The meeting agenda and registration form can be found on pages 6 and 7.


www.inisbrookgolfresort.com



NEW GemOro XSteam" Collections of the properties of the state of the s



NEW GemOro UtraSteami




NEW GemOro Britiant Spaf



NEW GemOre Bench Lamp lwn lubo

Water buylagen legter tij men. Utsak ital 10 Black ligger blad og e 20% og a utselt av tre. Net e legter parkers gestertagemen 20 og ikkeljen, de



NEW GemCro Diamond Magnifier Light 2.25x




NEW GemOro 0800


Available for Immediate Shipmenti

SUPERIOR INSTRUMENTS



renata batteries





GemOro Brilliant Spa™


- The personal size steamer that professionally cleans diamonds, gold, silver and platinum iewelry
- Powerful high-pressure steam safely blasts away dirt, grime, oil and more
- Includes plastic coated stainless steel jewelry holding tweezers, removable stainless basket and water funnel with measuring fill cup
- Designed for safety ETL Listed
- Advanced LED indicator lights show when unit is heating and when it is ready to steam
- · Convenient blue LED light illuminates jewelry while being steam cleaned
- · Easy-lift handles for moving
- Cabinet made of durable, long-life ABS, with contemporary stainless steel accent panels
- Compliments sister product: GemOro Sparkle Spa™ Personal Ultrasonic Jewelry Cleaner
- Designed in the USA with European influence
- One Year Limited Replacement Warranty

Stock #0360 List Price \$99.95 Introductory Sale Price \$4995

Quantity Orders 1-2 Units 3-5 Units 6+ Units \$4995 \$4750 \$4495

GemOro UltraSteam™

The world's first patented combination ultrasonic & steam cleaner for jewelers.



- Patented combination professional steam cleaner with built-in ultrasonic.
- · Perfect size 1 pint tank capacity, this powerful ultrasonic cleaner generates 42,000 ultrasonic waves per second.
- · Ultrasonic includes stainless steel basket and cover with bright blue LED tank illumination.
- Digital control panel provides three ultrasonic cleaning cycles of 3, 6 and 9 minutes.
- · Built-in drain with removable drain fill reservoir for convenient ultrasonic tank water removal.
- · Steam cleaner safely generates high pressure up to 65PSI using regular tap water.
- Ideal size for retail jewelers with 1/4 gallon steamer tank capacity.
- · Easy to use button controls activates steam on demand for either continuous or burst steam options.
- Built-in yet removable stainless steel basket for holding jewelry during cleaning and while drying.
- Includes: Plastic coated stainless steel jewelry holding tweezers, stainless steel handheld minibasket with handle for holding diamond ear studs, etc. and water funnel with measuring fill cup.
- · Made of durable, long-life ABS.
- Built-in Easy-Lift™ handles for moving.
- Designed in the USA with European influence.
- · Convenient size fits on showcase or counter.
- Designed for safety ETL Listed.
- One Year Limited Replacement Warranty

Stock #0366 List Price \$325 Introductory Sale Price \$24995 Case 3:08-cv-00103 Document Cove Filed 01/23/2008 Page 21 of 21

The S-44 civil cover sheet and the information contained herein neither replace nor supplement the filing and service of pleadings or other papers as required by law, except as provided by local rules of court. This form approved by the Judicial Conference of the United States in September 1974, is required for the use of the Clerk of Court for the purpose of initiating the civil docket sheet. (SEE INSTRUCTIONS ON THE REVERSE OF THE FORM.) I. (a) PLAINTIFFS JEWEL JET, LP SY KESSLER SALES, INC. (b) COUNTY OF RESIDENCE OF FIRST LISTED COUNTY OF RESIDENCE OF FIRST LISTED PLAINTIFF Dallas County, Texas DEFENDANT Dallas County, Texas (IN U.S. PLAINTIFF CASES ONLY)
IN LAND CONDEMNATION CASES, USE THE (EXCEPT IN U.S. PLAINTIFF CASES) NOTE: 03.0 LOCATION OF THE TRACT OF LAND INVOLVED. CLERK, U.S. DISTRIC OF TEXA ATTORNEYS (FIRM NAME, ADDRESS, AND NORTHERN DISTRICT (c) ATTORNEYS (IF KNOWN) TELEPHONE NUMBER) Michael W. Shore, Justin Kimble Shore Chan Bragalone LLP UNKNOWN 325 N. St. Paul Street, Suite 4450 Dallas, Texas 75201 (214) 593-9110 11. BASIS OF JURISDICTION (PLACE AN "X" IN ONE BOX ONLY) III. CITIZENSHIP OF PRINCIPAL PARTIES (PLACE AN "X" IN ONE (For Diversity Cases Only) BOX FOR PLAINTIFF AND ONE BOX FOR DEFENDANT) PTF DEF PTF DEF 1 U.S. Government 3 Federal Question Plaintiff Incorporated or Principal Place (U.S. Government Not a Party) Citizenship of This State 1 1 1 of Business In This State X 4 X 4 П 2 U.S. Government 4 Diversity Incorporated and Principal □ 5 □ 5 Defendant (Indicate Citizenship of Parties Place of Business In Another in Item III) State Foreign Nation Citizen or Subject of a 3 3 3 Foreign Country NATURE OF SUIT (PLACE AN "X" IN ONE BOX ONLY) CONTRACT FORFEITURE/PENALTY BANKRUPTCY OTHER STATUTES PERSONAL INJURY PERSONAL INJURY ☐ 610 Agriculture ☐ 400 State Reapportionment 110 Insurance 422 Appeal 28 USC 158 120 Marine 130 Miller Act ☐ 310 Airplane ☐ 362 Personal Injury-410 Antitrust ☐ 620 Other Food & Drug Med. Malpractice ☐ 625 Drug Related Seizure ☐ 423 Withdrawal п 430 Banks and Banking 315 Airplane Product 140 Negotiable Instrument 28 USC 157 ☐ 450 Commerce/ICC Rates/etc. ☐ 365 Personal Injury-Liability of Property 21 USC 881 150 Recovery of Overpaymen Product Liability 460 Deportation ☐ 320 Assault, Libel & ☐ 630 Liquor Laws PROPERTY RIGHTS 1 470 Racketeer Influenced and ☐ 368 Asbestos Personal & Enforcement of Judgment Slander 640 R R & Truck ☐ 151 Medicare Act ☐ 330 Federal Employ Corrupt Organizations Injury Product 650 Airline Regs. ☐ 152 Recovery of Defaulted Student Loans Liability ■ 810 Selective Service
■ 850 Securities/Commodities/ ers' Liability ■ 820 Copyrights 660 Occupational ☐ 340 Marine ☐ 345 Marine Product PERSONAL PROPERTY 830 Patent Safety/Health (Excl. Veterans) ☐ 840 Trademark Exchange ☐ 370 Other Fraud ☐ 690 Other ☐ 875 Customer Challenge 12 ☐ 153 Recovery of Overpayment Liability 371 Truth in Lending of Veteran's Benefits USC 3410 350 Motor Vehicle 380 Other Personal LABOR SOCIAL SECURITY 160 Stockholders' Suits ☐ 355 Motor Vehicle ☐ 891 Agricultural Acts Property Damage 190 Other Contract Product Liability ■ 892 Economic Stabilization Act ☐ 385 Property Damage ☐ 710 Fair Labor Standards ■ 861 HIA (1395ff) 893 Environmental Matters 195 Contract Product Liability ☐ 360 Other Personal Injury Product Liability 862 Black Lung (923) Act 894 Energy Allocation Act ☐ 720 Labor/Mgmt 863 DIWC/DIWW (405(g)) REAL PROPERTY CIVIL RIGHTS ☐ 895 Freedom of PRISONER PETITIONS Relations 864 SSID Title XVI Information Ac 730 Labor/Mgmt 865 RSI (405(g)) ☐ 210 Land Condemnation ☐ 441 Voting ☐ 900 Appeal of Fee ☐ 510 Motions to Reporting & Disclo-220 Foreclosuure Determination Under Equal 442 Employment FEDERAL TAX SUITS Vacate Sentence sure Act 8 Access to Justice 230 Rent Lease & Ejectment 443 Housing/ Habeus Corpus: 740 Railway Labor Act ■ 870 Taxes (U.S. Plaintiff 240 Torts to Land Accommodations ■ 950 Constitutionality of ☐ 530 General 790 Other Labor 245 Tort Product Liability or Defendant) 444 Welfare State Statutes ☐ 535 Death Penalty Litigation 290 All Other Real Property 440 Other Civil Rights ■ 890 Other Statutory Actions ☐ 871 IRS - Third Party 540 Mandamus & Other 791 Empl. Ret. Inc. 26 USC 7609 550 Civil Rights Security Act ☐ 555 Prison Condition ORIGIN (PLACE AN "X" IN ONE BOX ONLY) Appeal to Transferred from District Judge Ø 1 Original ☐ 2 Removed from ☐ 3 Remanded from ☐ 4 Reinstated or ☐ 7 from Magistrate Judge ☐ 5 another district ☐ 6 Multidistrict Proceeding State Court Appellate Court Reopened (specify) Litigation VI. CAUSE OF ACTION (Cite the U.S. Civil Statute under which you are filing and write brief statement of cause. Do not cite jurisdictional statutes unless diversity.) Action under 35 U.S.C. § 271 et seq. for infringement of U.S. Patent No. 7,257,319 B1 VII. REQUESTED IN ☐ CHECK IF THIS IS A CLASS ACTION **DEMAND \$ unspecified** CHECK YES only if demanded in complaint: COMPLAINT: UNDER FR C.P. 23 JURY DEMAND: ☑ YES □ NO VIII. RELATED CASE(S) (See instructions): JUDGE Pending DOCKET NUMBER Pending (See attached sheet for other related cases.) DATE SIGNATURE OF ATTORNEY OF RECORD January 23, 2008 FOR OFFICE USE ONLY

RECEIPT #

AMOUNT ___

__ APPLYING IFP

JUDGE

MAG. JUDGE